



***NPTF Dry Seal Threaded Valves for use
on Aluminum Tanks for EPA Compliant Fuel Systems***

***INSTALLATION INSTRUCTIONS
PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING***

These valves are for use on fuel tanks to comply with the new CARB and EPA standards and meet the requirements of U.S.C.G. Safety Standards (July 31, 2011) for 40 CFR Parts 9, 60, 80 et al. (Control of Diurnal Emissions From Nonroad Spark-Ignition Engines and Equipment).

Note: Inspect valve fitting annually for corrosion, replace if necessary.

Series 0588T00 Tank Vent Valves (TVV)



1. These valves are designed to mount into 1" NPTF dry seal aluminum threaded receivers welded onto tanks. (receiver not supplied).
2. Thread valve into receiver and orient hose barb in the direction of the vent line. Do not use the hose barb as a lever to tighten valve.
3. Attach 5/16" vent hose onto hose barb and tighten using hose clamps in accordance with ABYC Fuel System Vent Hose Clamping Standards (H24 Table 3).

*The above referenced standards can be obtained from:

(1). American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403

(2) U.S. Coast Guard
Washington, D.C. 20593
(or your local C.G. office)

(3). E.P.A.
401 "M" Street S.W.
Washington, D.C. 20460