

1



USCG USCG



Flex Mount System

Figs. 1487 - 1490 Series L.E.D. Double Stack Navigation Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length

CONSTRUCTION:

- Black Polymer
- Pre-Wired with 3 Feet of 18/2-SO Cable
- Translucent color specific insert on top of light for easy identification
- Independent mounting bracket allows for easy interchange of light fixtures

Tech Info

- L.E.D.: Operates on 12/24 VDC or 120/240 VAC Systems
- No user serviceable parts
- Mounting screw size: 3/8"
- Height overall: 13-1/4"
- Vert. height upper*: 10-3/4"
- Vert. height lower*: 3-1/2"

**NOW AVAILABLE
3NM & 6NM
VERSIONS**



**Fig. 1487
Green & Red Side Lights**



**Fig. 1488
Masthead Light**



**Fig. 1489
Stern Light**

**Fig. 1489
Towing Light**



**Fig. 1490
All-Round Light**

Double Stack Light Ordering Info

Black Polymer Description	Visibility Arc	Visibility Miles	120/240 VAC Black Polymer Std. Pkg. 1 Pc.	12/24 VDC Black Polymer Std. Pkg. 1 Pc.	Ship Wt. Carton Lbs. Standard Pkg.
Red Side Light	112-1/2°	3	1487R00BLK	1487R01BLK	7.5
Green Side Light	112-1/2°	3	1487G00BLK	1487G01BLK	7.5
White Masthead Light	225°	6	1488000BLK	1488001BLK	7.4
White Stern Light	135°	3	1489000BLK	1489001BLK	7.5
Yellow Towing Light	135°	3	1489M00BLK	1489M01BLK	7.5
White All-Round Light	360°	3	1490000BLK	1490001BLK	7.2
White All-Round Light**	360°	6	1490H00BLK	1490H01BLK	7.2
Red All-Round Light	360°	3	1490R00BLK	1490R01BLK	7.2
Green All-Round Light	360°	3	1490G00BLK	1490G01BLK	7.2
Yellow All-Round Light	360°	3	1490M00BLK	1490M01BLK	7.2

MARINE NAVIGATION LIGHT CERTIFIED TO THE USCG AND '72 COLREGS BY IMANNA LABS IN ACCORDANCE WITH U.L. 1104 (A.B.Y.C. A-1104). FOR USE ON VESSELS OVER 20 METERS.

Fig. 1381000BLK Bracket for mounting Double Stack lights.



Special lights to meet local requirements are available upon request

**For Great Lakes use

Note: L.E.D.'s have no user serviceable parts

* Vertical height is the measurement from the mounting surface to the center of the lens.