

1

NEW PRODUCT



USCG USCG

3 nm

6 nm



Flex Mount System

Figs. 1477 - 1480 Series Single L.E.D. Navigation Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length
Single lights are also individual replacement lights for the 1487 to 1490 series double stack lights (Pg C-6)

CONSTRUCTION:

- Black or White Polymer
- Pre-Wired with 3 Feet of 18/2-SO Cable
- Translucent color specific insert on top of light for easy identification

**NOW AVAILABLE
3NM & 6NM
VERSIONS**

Tech Info

- L.E.D.: Operates on 12 /24 VDC or 120 and 240 VAC Systems
- Screw Size: 1/4"
- Height Overall: 6"
- Vert. Height*: 3-1/2"



Fig. 1477
Red & Green Side Lights

Fig. 1478
Masthead Light



Fig. 1479
Stern Light



Fig. 1479
Towing Light

Fig. 1480
All-Round Light

* Vertical height is the measurement from the mounting surface to the center of the lens.

MARINE NAVIGATION LIGHT CERTIFIED TO THE USCG AND '72 COLREGS BY IMANNA LABS IN ACCORDANCE WITH U.L. 1104 (A.B.Y.C. A-1104). FOR USE ON VESSELS OVER 20 METERS.

Single Light Ordering Info

Black Polymer Description	Visibility Arc	Visibility Miles	120/240 VAC Black Polymer Std. Pkg. 1 Pc.	12/24 VDC Black Polymer Std. Pkg. 1 Pc.	Ship Wt. Carton Lbs. Standard Pkg.
Red Side Light	112-1/2°	3	1477R00BLK	1477R01BLK	3.2
Green Side Light	112-1/2°	3	1477G00BLK	1477G01BLK	3.2
White Masthead Light	225°	6	1478000BLK	1478001BLK	3.1
White Stern Light	135°	3	1479000BLK	1479001BLK	3.2
Yellow Towing Light	135°	3	1479M00BLK	1479M01BLK	3.2
White All-Round Light	360°	3	1480000BLK	1480001BLK	3.0
White All-Round Light**	360°	6	1480H00BLK	1480H01BLK	3.0
Red All-Round Light	360°	3	1480R00BLK	1480R01BLK	3.0
Green All-Round Light	360°	3	1480G00BLK	1480G01BLK	3.0
Yellow All-Round Light	360°	3	1480M00BLK	1480M01BLK	3.0

Special lights to meet local requirements are available upon request

**For Great Lakes use

Note: L.E.D.'s have no user serviceable parts

Fig. 1381000BLK Bracket for mounting Double Stack lights.

