



Figs. 0004D, 0005D & 0007D Series Navigation Lights

Certified For Use on Vessels 20 Meters (65.6 ft.) to 50 Meters (164.0 ft.) in Length

Figs. 0004F, 0005F, 0007F Series Navigation Lights

F- Series Lights are Certified For Replacement Use Only* on Power Driven Vessels Under 20 Meters (65.6 Ft.) in Length



CONSTRUCTION:

- Bottom Opening, Complete with Mounting Bracket
- **D Series:** Sheet Metal, Preprimed Galvanized Steel, Polished or Chrome Plated Brass
- Single Contact Prefocus Socket
- **F Series:** Preprimed Galvanized Steel, Polished Brass

Tech Info

Bulb Not Included
D Series: 12 Volt
F Series: 12 or 32 Volt
 Screw Size: #10
 Height Overall: 8-1/2"
 Height Lens: 5-1/8"

IMPORTANT BULB DATA FOR D SERIES
 To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must use a PERKO Cat. No. 0373 bulb, as specified below.



Fig. 0004G

Fig. 0004R



Fig. 0005



Fig. 0007



Fig. 0007M

Ordering Info - D Series

Description	Galvanized Steel	Polished Brass	Chrome Plated Brass	Visibility Arc	Visibility Miles	12V Required Bulb	Ship Wt. Carton Lbs. Std. Pkg. 1 Pc.
Red Side Light	0004RD3GAL	0004RD3POL	0004RD3CHR	112-1/2°	2	0373003CLR	2.7
Green Side Light	0004GD3GAL	0004GD3POL	0004GD3CHR	112-1/2°	2	0373002CLR	2.7
White Masthead Light	0005D03GAL	0005D03POL	0005D03CHR	225°	5	0373005CLR	2.9
White Stern Light	0007D03GAL	0007D03POL	0007D03CHR	135°	2	0373001CLR	2.8
Yellow Towing Light	0007MD3GAL	0007MD3POL	0007MD3CHR	135°	2	0373002CLR	2.8

Ordering Info - F Series*

Description	Galvanized Steel	Polished Brass	Visibility Arc	Visibility Miles	12V Required Bulb	32V Required Bulb	Ship Wt. Carton Lbs. Std. Pkg. 1 Pc.
Side Lights (Pair)	0004F03GAL	0004F03POL	112-1/2°	2	0070DP1CLR	0070DP2CLR	5.0
Red Side Light	0004RF3GAL	0004RF3POL	112-1/2°	2	0070DP1CLR	0070DP2CLR	2.7
Green Side Light	0004GF3GAL	0004GF3POL	112-1/2°	2	0070DP1CLR	0070DP2CLR	2.7
White Masthead Light	0005F03GAL	0005F03POL	225°	3	0070DP1CLR	0070DP2CLR	2.7
White Stern Light	0007F03GAL	0007F03POL	135°	2	0070DP1CLR	0070DP2CLR	2.7
Yellow Towing Light	0007MF3GAL	0007MF3POL	135°	2	0070DP1CLR	0070DP2CLR	2.7

See Page C-35 & C-36 for Bulb Information.

SPARE PARTS ORDERING INFORMATION

Lenses: 112-1/2° Fig. No. 0259CL3, Specify RED or GRN.
 135° Fig. No. 0269CL3, Specify YLW or WHT.
 225° Fig. No. 0256CL3WHT.

Mounting Bracket: 0131000GAL or PLB.
 Spare Electric Adapter for "F" Series: 0290F03.
 For D Series: Single Contact Prefocus Socket Assembly, Complete with Stand, Bottom Plate and Gasket: 0294003PLB.

Fig. 0290

