



Navigation Light Sets

Double Stack Base Mount 2 Mile/3 Mile Certified (USCG 2nm/3nm)

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer
 Finish: Black or White
 Dimensions: Height: 8-5/8", O.D.: 3-5/16"
 Screw Size: #10
 Voltage: 12 or 24V (Bulb Included)
 Wattage: Upper: 25 watts
 Lower: 10 watts
 Amperage: 25 watt 10 watts
 12V: 2.08 amps 12V: .83 amps
 24V: 1.04 amps 24V: .42 amps

Fig. 0200TAB**



Double Stack Base Mount	Visibility Arc	Black Retail Pkg.	White* Std. Pkg.	Visibility Miles	Replacement Bulb
Tri-Color/White All-Round Light**	360°	0200TABDP1	0200TABW01	2/2	037512V25W/10W
Masthead/White All-Round Light	360°	0200MABDP1	0200MABW01	3/2	037512V25W/10W
Green/Red All-Round Light	360°	0200GRBDP1	0200GRBW01	2/2	037512V25W/25W

* 12 Volt Only

** For Use on Vessels Under Sail Alone.

For Pipe Mounting Bracket options, see Figs. 0222 & 0224 below.



Halyard Mount 2 Mile/3 Mile Certified (USCG 2nm/3nm)

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Black or White Polymer
 Stainless Steel Mounting Hardware
 Dimensions: Height: 7-1/8", O.D.: 3-5/16"
 Screw Size: No mounting screws required
 Voltage: 12 or 24V (Bulb Included)
 Wattage: 25 watt or 10 watt
 Amperage: 25 watt 10 watts
 12V: 2.08 amps 12V: .83 amps
 24V: 1.04 amps 24V: .42 amps

Fig. 0200SRH



Halyard Mount	Visibility Arc	Black Retail Pkg.	White* Std. Pkg.	Visibility Miles	Replacement Bulb
White All-Round Light	360°	0200SWHDP1	0200SWHW01	2	037512V10W
Red All-Round Light	360°	0200SRHDP1	0200SRHW01	2	037512V25W
Green All-Round Light	360°	0200SGHDP1	0200SGHW01	2	037512V25W

* 12 Volt Only



Pipe Mounting Brackets For Use on All 0200/0210 Series Base Mount Lights

Material: Black or White Polymer
 Includes Screws and Soft Mounting Gasket for Mounting Bracket to Light
 Dimensions: Tapped Pipe Size: 1/2",
 O.D. Overall: 3-5/16"

Mount	Black Retail Pkg.	White Retail Pkg.
Flat	0222DP0BLK	0222DP0WHT
Cone	0224DP0BLK	0224DP0WHT



Fig. 0222 - BLK



Fig. 0224 - WHT



Fig. 0224 Shown Mounted

Spare Parts Information for pages 26 and 27

Lens assembly part numbers are determined by replacing the last three digits of the Catalog Number with the letters "LNS" (example: 0200BT0LNS, for a Bi-Color Top Mount Lens Assembly). Replacement Bulb Sockets: (single and lower for double) Cat. No. 0093, (upper for double), Cat No. 0095.