

Combination Masthead/White All-Round Navigation Lights

3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

- Material: Polymer Top and Base, Zinc Alloy, Clear Polymer Lens and 3/4" Anodized Aluminum Tube
- Finish: Black and Chrome Plated
- Contacts: Gold Plated
- Screw Size: #8
- Voltage: 12V LED
- Wattage: 2.2 watts (each compartment)
- Amperage: 0.2 amps (each compartment)
- Features: Two light compartments (Masthead/Anchor)
 - Fig. 1683: **Fixed Mount** - one pole length
 - Fig. 1696: **Fixed Mount** - two pole lengths
 - Fig. 1697: **Fixed Mount Short Pole** - with pigtail leads
- Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less than 18" long, include adapters available for flat or "V" type 45° mounts and a notch for through base wiring.
 - Fig. 1681: **Horizontal Mount** - Folds down 90° in either direction opposite the plane of attachment plate of the mount.
 - Fig. 1684: **Vertical Mount** - Folds down 90° in either direction along the plane of attachment plate of the mount.

1696 Head Style



Fig. 1684
Vertical Mt.
(Shown)

Fixed & Folding Mount Options



Fig. 1681
Horizontal
Mount



Fig. 1684
Vertical
Mount



Fig. 1697
Fixed Mt.
Short Pole



Figs. 1683
and **1696**
Fixed Mount

Base Mount	Height Overall	Base Dimensions	Retail Pkg.	OEM Bulk Pkg.
Fixed Mt.	3-3/8"	1" x 2-5/8"	1683DP0CHR	1683000CHR
Fixed Mt.	5-3/8"	1" x 2-5/8"	1696DP1CHR	1696001CHR
Fixed Mt.	11-5/8"	1" x 2-5/8"	1696DP2CHR	1696002CHR
Fixed w/Pigtail	4-1/8"	3/4" Dia.	1697DP0CHR	1697000CHR
Folding				
Horiz. Mt.	13-1/2"	2" x 1-1/2"	1681DP0CHR	1681000CHR
Vert. Mt.	13-3/8"	2-1/4" x 5/8"	1684DP0CHR	1684000CHR

Wiring Note: When choosing LED upgrades to replace existing incandescent combination masthead/all-round lights, optional Cat. No. 1680DP012V Converter Module is available to avoid re-wiring the navigation light switch.




Fig. 1680DP012V

Spare Parts Information

L.E.D.'s have no user serviceable parts

Replacement bases for Figs. 1681 & 1684 see page 41