

White All-Round Navigation Lights - Removable Plug-in Mount

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

- Material:** Polymer Top and Collar with Clear Fluted Lens and 3/4" Aluminum Tube
- Contacts:** Gold Plated
- Tube:** 3/4" Anodized Aluminum
- Voltage:** 12V (Bulb Included)
- Wattage:** 9 watts
- Amperage:** .69 amps
- Base (2-Pin):** Locking collar fits Figs.1045, 1046, 1047, & 1060 bases
Threaded collar fits Fig. 1048 base
- Features:** The Original Reduced Glare advanced globe design helps preserve night vision by reducing the amount of light wasted outside of the visibility zone and not attracting as many bugs.

0238 Style
Inland Series



Fig. 1440
(Shown)
Locking Collar
0° Rake

Fig. 1445
(Shown)
Locking Collar
5° Rake

Approx. Pole Length	Catalog Number	Pole Rake, Collar, & Pkg. Type
24	1440002CHR	
30	1440003CHR	
36	1440004CHR	Pole Rake: 0°
42	1440005CHR	Collar: Locking
48	1440006CHR	Package Type: OEM Bulk
54	1440007CHR	
60	1440008CHR	
24	1445002CHR	
30	1445003CHR	
36	1445004CHR	Pole Rake: 5°
42	1445005CHR	Collar: Locking
48	1445006CHR	Package Type: OEM Bulk
54	1445007CHR	
60	1445008CHR	
36	1622004CHR	Pole Rake: 5°
42	1622005CHR	Collar: Threaded
48	1622006CHR	Package Type: OEM Bulk
54	1622007CHR	
60	1622008CHR	

Compatible Bases (2-Pin)



Fig. 1045
0° Rake

Fig. 1047
0° Rake

Fig. 1046
5° Rake

Fig. 1060
5° Rake

Fig. 1048
5° Rake

Bases Sold Separately - See Pages 58 & 59.



Fig. 0238



Spare Parts Information

Bulbs: 0338DP2CLR.
Globe: 0238DP0BLK.



Fig. 0338