



## **Deck Connections & Cable Outlet**

## **Watertight Deck Connections**

Material: Fig. 1189 Brass

Fig. 1190 Zinc Alloy

Finish: Chrome Plated

Dimensions: Height: 1-3/16", Diameter: 1-5/8"

Screw Size: #6

Voltage:

Rated: 15 Amps at 12, 24 and 32 Volts Polarized Double

Contact Connector. Accepts up to #14 gauge

stranded wire 12, 24, or 32V

Features: Includes flange gasket with integral waterproof cap

for base when plug is removed



Fig. 1189 Chrome Plated Brass Fig. 1190 Chrome Plated Zinc



FinishRetail Pkg.OEM Bulk Pkg.Chrome Brass1189DP0CHR1189000CHRChrome Zinc1190DP0CHR1190000CHRNote: These Items Are Not Ignition Protected.

<u>Spare Parts Ordering Information</u> Connector with Cover: 1189DP099A.

Connector Only: 0042.

## **Watertight Cable Outlet**

Material: Brass

Finish: Chrome Plated
Dimensions: Diameter Base: 1-1/4"

Screw Size: #4

Features: • For 5/16 Inch O.D. Cable

• Equipped with Rubber Grommet for Watertight

Passage of Cable



Fig. 0424 Chrome Plated Brass

Finish Retail Pkg.
Chrome 0424DP0CHR

