



MOUNTING INFORMATION

Read all instructions before proceeding.

- 1). These instructions show the orientation of the light after the proper mounting location has been determined.
- 2). These lights are supplied with the proper circuit for operation on a nominal 12 volt system.
- 3). These lights contain no user serviceable components.
- 4). Draw a 8-1/2 inch long reference line through the center of the selected mounting location.
- 5). Cut out the mounting template below. Tape it on the mounting surface such that the reference line (drawn above) passes through the exact center of the template.
- 6). Drill four holes through the template as indicated for the #6 mounting screws and two or three holes 3/32" to 1/8" diameter to accommodate the wiring as indicated on template.
- 7). Wiring should be done by a qualified marine electrician. Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33CFR 183)* **Observe polarity.**
- 8). Attach the light to the mounting surface using #6 mounting screws.

* The above referenced standards can be obtained from:

- (1). American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403
 - (2). U.S. Coast Guard
Washington, D.C. 20593
(or your local C.G. office)
- Perko, Inc.
16490 N.W. 13th Avenue
Miami, FL. 33169-5707
www.perko.com
- 03/09
0606INS1

MOUNTING TEMPLATE

