

## Removable Bi-Color Pole Lights

**LED 2-mile (USCG 2nm) Certified** - Patent #D652,161S  
*Use on Power Driven Vessels Under 20m (65.6 ft.) in Length*

Material: Stainless Steel and Polymer Top  
 Finish: Polished with Black Top and Collar  
 Pole Rake: 0°  
 Tube: 3/4" Anodized Aluminum  
 Contacts: Gold Plated  
 Collar: Locking  
 Voltage: 12V LED  
 Wattage: 2.6 watts  
 Amperage: 0.2 amps  
 Base (2-Pin): 1045 or 1047

**STEALTH II Series**



Fig. 1617



Pole Length	Retail Pkg.	OEM Bulk Pkg.
12"	1617DP2BLK	1617002BLK
17-3/8"	1617DP3BLK	1617003BLK

**1-mile (USCG 1nm) Certified** - Patent No. 4,500,947  
*Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length*

Material: Polymer Top  
 Finish: Black Top and Collar  
 Pole Rake: 0°  
 Tube: 3/4" Anodized Aluminum  
 Contacts: Gold Plated  
 Collar: Locking  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts  
 Amperage: .80 amps  
 Base (2-Pin): 1045 or 1047



Fig. 1612



**PROP 65 WARNING**  
 (Contains Lead)

Pole Length	Retail Pkg.	OEM Bulk Pkg.
12"	1612DP2BLK	1612002BLK
17-3/8"	1612DP3BLK	1612003BLK

NOTE: Fig. 1612 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24 volt applications on new construction.

### Compatible Bases (2 Pin)



Bases Sold Separately - See Pages 58 & 59.

### Spare Parts Information

**FIG. 1617:**  
 L.E.D.'s have no user serviceable parts

**FIG. 1612:**  
 Bulbs : 0071DP0CLR.  
 Lens Set: 0283DPALNS.



Fig. 0071 DP0CLR



Fig. 0283 DPALNS