

LED Navigation Light Sets

Base Mount 2 Mile/3 Mile LED Certified (USCG 2nm/3nm)

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer
 Finish: Black or White
 Dimensions: Height: 3-13/16", O.D. Base: 3-5/16",
 Screw Size: #10
 Voltage: 12/24 VDC LED
 Wattage: 2.6 watts
 Amperage: 0.2 amps



Fig. 0210 Base Mount Green Side light

Base Mount	Visibility Arc	Black Retail Pkg.	White Std. Pkg.	Visibility Miles
Red Side Light	112-1/2°	0210PB0DP1	0210PB0W01	2
Green Side Light	112-1/2°	0210SDBDP1	0210SDBW01	2
White Masthead Light	225°	0210MB0DP1	0210MB0W01	3
White Stern Light	135°	0210SNBDP1	0210SNBW01	2
Yellow Towing Light	135°	0210TWBDP1	0210TWBW01	2
White All-Round Light	360°	0210SWBDP1	0210SWBW01	2
Red All-Round Light	360°	0210SRBDP1	0210SRBW01	2
Green All-Round Light	360°	0210SGBDP1	0210SGBW01	2



For Pipe Mounting Bracket options see Figs. 0222 & 0224 on page 27

2

Navigation Lights

Top Mount 2 Mile/3 Mile LED Certified (USCG 2nm/3nm)

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Black or White Polymer
 Dimensions: Top Mt: Height: 4-13/16", O.D.: 3-5/16", Projection: 3-5/16"
 Screw Size: #8
 Voltage: 12/24 VDC LED
 Wattage: 2.6 watts
 Amperage: 0.2 amps
 Features: Stainless Steel Mounting Bracket Included



Fig. 0210 Top Mount Masthead

Top Mount	Visibility Arc	Black Retail Pkg.	White Std. Pkg.	Visibility Miles
Red Side Light	112-1/2°	0210PT0DP1	0210PT0W01	2
Green Side Light	112-1/2°	0210SDTDP1	0210SDTW01	2
White Masthead Light	225°	0210MT0DP1	0210MT0W01	3
White Stern Light	135°	0210SNTDP1	0210SNTW01	2
Yellow Towing Light	135°	0210TWTDP1	0210TWTW01	2



Spare Parts Information

Note: L.E.D. lights have no user serviceable parts