

Masthead Lights

3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length


- Material: All Polymer
 Finish: Black
 Dimensions: Height: 7", Width: 4-1/8", Projection: 4-3/4"
 Screw Size: #10
 Voltage: 12V LED or Incandescent (Bulb Included)
- | | | |
|-----------------------|---------------------|------------|
| <u>Masthead Light</u> | <u>Incandescent</u> | <u>LED</u> |
| Watts: | 10 watts | 5.6 watts |
| Amperage: | .83 amps | 0.4 amps |
| <u>Spreader Light</u> | | |
| Watts: | 20 watt | 2.2 watts |
| Amperage: | 1.56 amps | 0.18 amps |
- Features: Bottom light works as a Combination Spreader and Deck Illumination Light

Combination Masthead/Deck Spreader Light



Fig. 0170BMD LED

Light Type	Retail Pkg.	Std. Pkg.
Incandescent	0170BMDDP1	0170BMD12V
LED	-----	0170BMD12L



LED Spreader Light

Fig. 0170BMD Incandescent



2-mile Certified A-16 for replacement use only

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

- Material: Brass or Stainless Steel Top, Polymer Base
 Finish: Chrome Plated or Polished
 Dimensions: O.D. Base: 2-3/8", Height: 1-5/8"
 Screw Size: #4
 Contacts: Gold Plated
 Voltage: 12V (Bulb Included)
 Wattage: 10 watts
 Amperage: .80 amps



Fig. 0964 Masthead

Finish	Retail Pkg.
Chrome Plated	0964DP0CHR
Polished SS	0964DP0STS



Fig. 0964 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 12 or 24 volt applications on new construction.

Spare Parts Information

Fig. 0170 BMD:
 Masthead Bulb: 0070DP1CLR.
 12V Halogen Bulb for Deck Spreader Light: 006812V20W.
 L.E.D.'s have no user serviceable parts



Fig. 0070DP1CLR

Fig. 0964:
 Lens (Open Top): 0281DPAWHT.
 Lens (Closed Top): 0295DPOWHT.
 Bulbs: 0071DP0CLR.
 Base with Socket Assembly: 0135.



Fig. 0071DP0CLR

Fig. 0295

Fig. 0281