



LED White All-Round Navigation Lights - Removable Plug-in Mount

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer Top and Collar with Clear Fluted Lens,

Frosted Top, and 3/4" Aluminum Tube

Contacts: Gold Plated Voltage: 12V LED Wattage: 4.5watts Amperage: 0.35 amps

Base (2-Pin): Locking collar fits Figs. 1045, 1046, 1047,

1059, & 1060 bases

Threaded collar fits Fig. 1048 base

Features: The "Reduced Glare" advanced globe design helps

preserve night vision by reducing the amount of light wasted outside of the visibility zone and offers improved visibility when in rough water and from

above.

LED: Sealed from the Environment

Retail Pkg.: Omega Series - Universal replacement lights are

designed to fit most other manufacturers' bases. They feature two collars (one threaded and one locking), two screw positions, and an adjustable head (wide 40°). Adjustability of the globe allows for proper horizontal alignment regardless of base

configuration.

OEM Bulk Pkg.: These lights have fixed pole light heads with either

 0° or 5° pole rake and single locking or threaded

collar

Approx. Pole	Catalog Number	Pole Rake, Colla	ar, & Pkg. Type
Length 36 48	1343DP4CHR 1343DP6CHR	Pole Rake: Collar: Package Type:	Adjustable Locking & Threaded Retail
24 30 36 42 48 54 60	1440L02CHR 1440L03CHR 1440L04CHR 1440L05CHR 1440L06CHR 1440L07CHR 1440L08CHR	Pole Rake: Collar: Package Type:	0° Locking OEM Bulk
24 30 36 42 48 54	1445L02CHR 1445L03CHR 1445L04CHR 1445L05CHR 1445L06CHR 1445L07CHR 1445L08CHR	Pole Rake: Collar: Package Type:	5° Locking OEM Bulk
36 42 48 54 60	1622L04CHR 1622L05CHR 1622L06CHR 1622L07CHR 1622L08CHR	Pole Rake: Collar: Package Type:	5° Threaded OEM Bulk



Compatible Bases (2-Pin)



Spare Parts Information

L.E.D.'s have no user serviceable parts

Bases Sold Separately - See Pages 58 & 59.