

## Specialty Lights

### Heavy Duty Pole Lights & Bases

#### 2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

#### Poles:

Material: Fig. 0390: Marinium Top and Clear Fresnel Globe  
 Fig. 0390L: White Polymer Top and Clear Fluted Lens  
 Fig. 0394: Black Polymer Top and Clear Fluted Lens  
**Tube: 7/8" Anodized Aluminum with Marinium Collar**

Rake: 0°

Voltage: Fig. 0390L: 12V LED  
 Fig. 0390/0394: 12V (Bulb Included)  
 Fig. 0390L Fig. 0390 Fig. 0394

Wattage: 4.5 watts 9 watts 9 watts  
 Amperage: .35 amps .69 amps .69 amps

Features: Fig. 0394 • Rotates 90° in Both Directions (Includes Fig. 0477 Pole Clip)  
 (See page 54)

#### Bases:

Material: Marinium Alloy Base & Cap with Polymer Gasket and Retainer  
 Tube: Fits 7/8" Anodized Aluminum Poles  
 Rake: 0°

#### Head and Base Options



Fig. 0390

Fig. 0390L  
LED

Fig. 0392  
Vertical Mt.

Fig. 0393  
Vertical Mt.

Poles Length	Light Type	OEM Bulk Pkg.
48	Bulb	0390006MAR
54	Bulb	0390007MAR
60	Bulb	0390008MAR
48	L.E.D.	0390L06MAR
54	L.E.D.	0390L07MAR
60	L.E.D.	0390L08MAR



Bases Projection	Dimensions	Screw Size	Retail Pkg.	OEM Bulk Pkg.
-----	2-3/8" O.D.	#8	0391DP0MAR	0391000MAR
2-3/16	3-1/16" x 3-3/8"	#10	-----	0392000MAR
2-3/16	3-1/16" x 4-1/2"	#10	-----	0393000MAR

Cap, Retainer, and Gasket for Fig 0391 Base: 0391DP099A.  
 Cap, Retainer, and Gasket for Fig 0392 Base: 0392DP099A.  
 Cap, Retainer, and Gasket for Fig 0393 Base: 0393DP099A.

#### Folding Pole & Base Combination (See Page 54)

Pole Length	Projection Base	Base Dimensions	Screw Size	OEM Bulk Pkg.
36	2-3/16"	3-1/16" x 4-1/2"	#10	0394000MAR

Fig. 0390L Pole (Shown)



Fig. 0391 Threaded Collar 2 Pin Base

