



**Cat. No. 0362 Series White All-Round Light**  
**Cat. No. 0371 Series White All-Round Light**

The above lights are designed for use on sail or power driven vessels under 20 meters (65.6 ft.) in length, operating on a 12 volt nominal system. In order to comply with the '72 COLREGS and the U.S. Inland Rules, the following must be adhered to:

### **MOUNTING INFORMATION**

**Read all instructions before proceeding.**

- 1). For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A- 16\*, the '72 COLREGS\*, and the U.S. Inland Rules\*.
- 2). These lights are designed to be mounted on a horizontal surface (Cat. No. 0371 Series) or on a vertical, 1/2 inch threaded pipe (Cat. No. 0362 Series).
- 3). Horizontal rotation of these lights is unimportant, as all-round lights have a 360' horizontal arc of visibility.
- 4). Cat. No. 0371 Series:  
Unscrew globe from body. Using base as a template, mark the mounting surface and drill to accommodate two #8 flat head screws. Then drill an electrical supply clearance hole located approximately in the center of the two mounting holes on the mounting surface. Attach supply connections to the light and reassemble, making sure to wire in accordance with both A.B.Y.C. Standard E-9\* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)\*. Fasten light to the mounting surface.
- 5). Cat. No. 0362 Series:  
Make sure to wire in accordance with A.B.Y.C. Standard E-9\* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)\*. Run the supply wire out of the top of the mounting pipe. Attach supply connections to the socket. Screw the body onto the mounting pipe, and seal the pipe connection with compound or teflon tape. Prevent twisting the wire inside the pipe when attaching the light by twisting the light a few times counter-clockwise before mounting.
- 6). The bulb listed below must be used in order to comply with the navigation regulations cited above. ANSI #90, 12 volt 6 C.P. Bulb (PERKO Cat. No. 0337011DP 12V, 7W).

The above referenced standards can be obtained from:

- |   |  |
|---|--|
| (1). American Boat & Yacht Council, Inc.<br>613 Third Street, Suite 10<br>Annapolis, MD 21403 | (2). U.S. Coast Guard<br>Washington, D.C. 20593<br>(or your local C.G. office) |
|---|--|